

# THE DOW CHEMICAL COMPANY LOUISIANA OPERATIONS

### SHUTDOWN APPLICATION for POWER I PLANT'S BOILER 3 & 4

Submitted to:
Office of Environmental Services
Permits Division
Louisiana Department of Environmental Quality

P.O. Box 82135 Baton Rouge, Louisiana

March 31, 2005

For Information Contact:
David Wesson
Environmental, Health, and Safety Services
THE DOW CHEMICAL COMPANY
Louisiana Operations
P. O. Box 150

Plaquemine, Louisiana 70765-150



original to

March 30, 2005

MAINFILE

The Dow Chemical Company P.O. Box 150 Plaquemine, Louisiana 70765-0150

CERTIFIED MAIL RETURN RECEIPT REQUESTED

Dr. Chuck Brown Assistant Secretary Office of Environmental Services Department of Environmental Quality P.O. Box 4313 Baton Rouge, Louisiana 70821-4313

**BOILER 3 & BOILER 4 SHUTDOWN APPLICATION** AI 1409 POWER I PLANT, PERMIT 385 (M-3) THE DOW CHEMICAL COMPANY, LOUISIANA OPERATIONS

Dear Dr. Brown:

Pursuant to the requirements of Section 33:III.525 of the Louisiana Administrative Code (LAC), the Dow Chemical Company, Louisiana Operations (Dow), is submitting the enclosed shutdown application for those decommissioned sources operated under Louisiana State Air Permit No. 385 (M-3) for the Power I Plant. The Louisiana Division Complex is designated as a Part 70 major source as defined in LAC 33:III.507.A.1.a. The Power I Plant's air permit, 385 (M-3) was granted on August 8, 1993.

Attached is the Application for Approval of Emissions of Air Pollutants (Appendix A). The Power I Plant shutdown Boiler 3 on March 12, 2004 and Boiler 4 on March 19, 2004. This attached application has updated EIQs reflecting the deletion of sources. Also attached for reference are the ERC Bank Applications documents, VOC-23 and NOX-9 for the decrease in emissions from the shutdown of Power I's boilers, Boiler 3 (EIQ 1E) and Boiler 4 (EIQ 1F). This documentation includes the Certificate Applications for each of the Emission Reduction Credits (Appendix B) and background calculations (Appendix C) to show how the Emission Reduction Credits were determined. As defined in LAC 33:III.607.A.4 at time of generation, Boilers 3 and 4 VOC and NOx emission reductions have been reviewed and determined to meet the definition. Dow is acknowledging that state permit 385 (M-3) has expired with the shutdown of Boilers 3 and 4.

Additional information will be submitted at a later date concerning the readjustment of permitting fees in associated with the above equipment shutdown.

If you should have questions concerning this application, please don't hesitate call me at (225) 353-66993

Regards.

Denise Hale
Environmental, Health, and Safety Services

Attachments

LANT64\Env Air\Title V Permits\Power&Utilities\TitleV\2005 Shutdown\Boiler 3&4\Boiler 3&4 Cover Letter.doc

Department of Environmental Quality Permits Division P.O. Box 82135 Baton Rouge, LA 70884-2135

### **LOUISIANA**

# **Application for Approval of**



(	(225) 765-0219	En	nissions	of Air	Poll	utantș	3	1	
1	Company Name The Dow Chemical Con	l npany, Louisiana	Operations			ner erator		≓or Remits t	Division Use On
Please Type or	Parent Company (if Company Name given above is a division)  The Dow Chemical Company								
Print	Plant Name (if any)								
	Power I Plant								
	Nearest Town		Parish wher	e locate	ıd				1:31
	Piaquemine, LA		iberville/We	est Bate	on Roug	ge		<b>3</b> 7 8 7	
	Agency Interest Number		CDS Numbe	er					
	1409	· · · · · · · · · · · · · · · · · · ·	1280-00008						
PROPOSE	ED ACTION Give a bri understar	ef description of p	roposed action	n. Attac	h flow d	iagrams,	illustrat	ions required	to convey an
	ation is to shutdown Bollers 3	Ū							
DISTANC	E TO (km): Texas	242	Arkansas _	300	Mis	sissippi	76	Alabama	322
LATITUDE	E OF FACILITY FRONT GAT	E: <u>30</u>	_ DG _	18	MN	50	SEC		
LONGITU	DE OF FACILITY FRONT G	ATE: 91	_ DG _	14	MN	26	SEC		
The Louisia on Louisian	n the attached figures, the Pona Operations facility is loca a Highway 1 (See Figure 1).  APPLICATION	wer i Plant is lock ted on the west ba	ated inside the ank of the Miss	Louisia sissippi	na Ope River in	rations fa the paris	cility of hes of l	The Dow Che berville and V	emical Compan; Vest Baton Rou
Part	: 70 <b>☑</b> Sta	ate	Gene	ral				Renewal (Par	rt 70)
Enti-	rely new facility		F	Reconci	liation			<u> </u>	,
Prev	viously grandfathered, exemp	oted or unpermitte	d 🗌 h	/lodifica	tion or e	xpansion	of exis	ting facility	
PROJECT F	EE CALCULATION: Enter f	ee number, permi	t type, product	tion cap	acity/thr	oughput,	and fee	amount purs	suant to
	FEE NO.		TYPE		O	APACITY	,		AMOUNT
	N/A	Emissi	on Reduction	-		onfidenti	ai		N/A
KEY DAT	ES								
Estimate	ed date construction will com	mence:	N/A	Esti	mated d	ate opera	ation wil	l commence:	N/A

Note: A completed Emission Inventory Questionnaire (EIQ) that reflects projected emissions from your facility as a whole after the project described in this application becomes operational must be submitted with this application. If you are submitting an application that is for modification or expansion of an existing facility, the Department of Envionmental Quality must also have an EIQ for existing emissions. If you have already submitted an EIQ that is on file with the Department, it may fulfill this requirement. Consult instructions for runther details.

#### **6 EMISSIONS BY POLLUTANT**

List each emission from all sources. Group by pollutant PM10, SO2, NOx, CO, VOC Air Toxics, Non-VOC Air Toxics, Other VOC, Non-VOC/Non-TAP, and Total VOC. Grouping by SARA VOC and SARA Non-VOC is optional. Show total tons/year for each pollutant. Consult instructions.

Emission Point ID Number	Pollutant (List individual toxics and non-criteria hydrocarbons separately)	Permitted Emission Rate Before	Permitted Emission Rate After
		tons/yr	tons/yr
	See EIQ sheets		

#### 7 HISTORY OF PERMITTED EMISSIONS

List each emission level from facility permits (for unit specific permits, the history should be for the unit of concern only). Group by permit and show totals. Include as last entry, the total emissions following the proposed change, entering the project name for "Permit number" and date of submittal for "Date permit issued". Consult instructions.

Permit Number	Date Permit Issued	Pollutant	Permitted Emission Rate (tons/yr)
385 (M-3)	8/11/1993	CARBON MONOXIDE	1348.6
		NITROGEN OXIDES	9796.0
		PARTICULATE MATTER	77.0
		SULFUR DIOXIDE	258.9
		TOTAL VOC (INCL. LISTED)	25.3

#### **EMISSION POINT LIST**

# Power I Plant The Dow Chemical Company, Louisiana Operations Plaquemine, LA

Emission Point	Description	Operating Rate (Max) or Tank Capacity	Operat H/D	_	hedule W/Y
1E	Boiler #3	1020 MM BTU/hr	24	7	52
1F	Boiler #4	1603 MM BTU/hr	24	7	52

#### ANNUAL EMISSION RATES

Emission		Permitt	ted emission rates	are listed in tons	per year	
Point	PM/PM10	SO2	NOx	CO	VOC	Other**
		see ElQ:	sheets			

Statement for Applicable Requirements for Which the Source Is In Compliance

Based on information and belief, formed after reasonable inquiry, The Dow Chemical Company is in compliance with and will continue to comply with all applicable requirements pertaining to the sources covered by the permit application, as outlined in Table 1 through Table 5 in the permit application.

For requirements promulgated as of the date of this certification with compliance dates effective during the permit term, I further certify that The Dow Chemical Company will comply with such requirements on a timely basis and will continue to comply with such requirements.

CERTIFICATION: I certify, under provisions in Louisiana and United States Law which provide criminal penalties for false statements, that based on information and belief formed after reasonable inquiry, the statements and information contained in this Application for Approval of Emissions of Air Pollutants, including all attachments thereto and the compliance statement above, are true, accurate, and complete.

CERTIFICATION: I certify that the engineering calculations, drawings, and design are true and accurate to the best of my knowledge.

1	1	P	F	R	S	റ	N	i٨	ı۶	-1	

#### a. Responsible Official

(225) 353-1642		
Plaquemine Business Phone	LA	70765
City	State	Zip
P. O. Box 150		
Street or P.O. Box		
Louisiana Operations		
Suite, mail drop, or division		
The Dow Chemical Company		
Company		
Production Leader		
Title	-	
Gretchen LeBlanc		
Name		

#### b. Professional Engineer

Name		
Bruce Alexius		
Title	••	
Expertise Center Manager		
Company		
The Dow Chemical Company		
Suite, mail drop, or division		
Louisiana Operations		
Street or P.O. Box	,	
P. O. Box 150		
City	State	Zip
Plaquemine	LA	70765
Business Phone	I	
(225) 353-8844		

C
Signature of responsible official(s) (See 40 CFR 70.2)
1 - 2
1 Both Kon ("10-NOMI)
Gretchen Cletlane
V5-1-
3/23/05
ろ <i> 2名 /)</i> 名
· · · · · · / · · · · · · · · · · · · ·
,
Date

Signature of Professional Engineer
Bouce J. Mefus
Date
3/22/05
Louisiana Registration No.
188 AGMINING
LINE OF LOUIS
\$ * * * * * * * * * * * * * * * * * * *
BRUCE J. ALEXIUS
FROFESSICIAL ENGINEERS
IN SE
The same of the line
BRUCE L'ALEXIUS License No. 18845 OF PROFESSIONAL EMPRES IN TAL ENGINEER
***************************************

Department of Environmental Quality
Permits Division
P. O. Box 82135
Baton Rouge, Louisiana 70884-2135
(225) 765-0219

### **LOUISIANA**

	Emission	Inventory Qu for Air Poll		(EIQ)
1	Company Name The Dow Chemical Company, L	ouisiana Operations	Owner Operator	For Permits Division Use Only
Please Type	Parent Company (if Company Na The Dow Chemical Company			
or Print	Plant Name (if any) Power I Plant			
	Nearest town Plaquemine, LA	Parish where locate lberville/West Bat	-	
	Agency Interest Number	CDS Numbe	<b>T</b>	
2 TYPE OF EIQ	✓ a. ONLY presently exis	applica emissio	tion for a permit, va ins expected to be s	emissions associated with an emissions riance, or exemption AND presently existing still existing after facility or modification ecomes operational.
3 CONFIDENTIA	LITY If you are requesting confide (You must attach justificatio			on emission rates, check box
Days per year fact Peak production so Daily operating so Approximate num	mally NOT operating: Mon ility typically operates: 365 season (list months): Not seasor thedule 24-hours OR specify number of employees at this locaton: a that, as a whole, operate intermittents.	mber of hours 1,700	ed 🗆 Thu	□ Fri □ Sat □ Sun
•	n, partnership, or sole proprietorship		regulated utility other, specify	municipal government
	y Indicate Standard Industrial Clas 2869 2821			:
	eration with emphasis on air pollution t is a steam/power cogeneration facil		ents if more space is	s needed.
,				

#### 5 SUMMARY OF EMISSIONS FOR ENTIRE PLANT AS A WHOLE

Rates given should correspond in most cases to the sum of the individual average rates of the point sources listed on the Single Point Source/ Area Source forms.

Emission Rate lbs/hr	Emission Rate tons/yr	
0	0	
0	0	
0	0	
0	0	
0	0	
	lbs/hr	

#### 6 PERSONNEL

خ	Manager	Λf	Eacility.	OΠ	<b>location</b>	٥t	nlant	cite
a.	Manayer	vi	гасшцу	OH	location	a١	Piani	2110

Name		
Gretchen LeBlanc		
Title		•
Production Leader		
Company		
The Dow Chemical Company	1	
Suite, mail drop, or division		
Louisiana Operations		
Street or P.O. Box		
P. O. Box 150		
City	State	Zip
Plaquemine	LA	70765
Business Phone		
(225) 353-1642		

b. Person to contact at site about air pollution control

Name		
Denise Hale		
Title		·····
Senior Environmental Specialist		
Company		
The Dow Chemical Company		
Suite, mail drop, or division		
Louisiana Operations		
Street or P.O. Box		
P. O. Box 150		
City	State	Zip
Plaquemine	LA	70765
Business Phone	•	
(225) 353-6699		

c. Headquarters of other off-site contact (see instructions)

Name		
N/A		
Title		
N/A		
Company		
N/A		
Suite, mail drop, or division		
N/A		
Street or P.O. Box		
N/A		
City	State	Zip
·N/A	N/A	N/A
Business Phone		
·N/A ,		

d. Person who prepared this report

_ a	□ ь	C c	other (spec	ify below)
Name		•		
Kristin	a Boudre	aux		
Title				
Engine	er			
Compan	ıy			
Dow C	hemical C	ompany		
Suite, m	ail drop, or	division		
P. O. B	ox 150			
Street o	r P.O. Box			
City			State	Zip
Plaque	mine		LA	70765
Busines	s Phone			
(225) 3	53-5785			

CERTIFICATION: I certify, under provisions in Louisiana and United States Law which provide criminal penalties for false statements, that based on information and belief formed after reasonable inquiry, the statements and information contained in this Emission Inventory Questionnaire (EIQ) for Air Pollutants, including all attachments thereto, are true, accurate, and complete.

Signature of responsible official(s) (See 40 CFR 70.2)
Grefchen Clessan
Date
3/23/05
,
Date

Department of Environmental Quality Permits Division P.O.Box 82135 Baton Rouge, LA 70884-2135 (225) 765-0219	ronmental Quality Division 82135 A 70884-2135 5-0219	!	Ø	LOUISIANA SINGLE POINT/AREA/VOLUME SOURCE Emission Inventory Questionnaire (EIQ) for Air Pollutants	LOUISIANA GLE POINT/AREA/VOLUME SOUR Emission Inventory Questionnaire (EIQ) for Air Pollutants	LOUISIANA INT/AREA/VOLUM Inventory Questionn for Air Pollutants	NA DLUMI stionna ants	E SOU ire (EIC	RCE				LOKO L
Company Name			ă	Plant location and name (if any)	d name (if an	(Au	:						Date of Submittal
The Dow Chem	The Dow Chemical Company, Louisiana Operation	uisiana Op		Power I Plant	<b>±</b>				Plaqu	Plaquemine, LA	5		March 2005
Source ID Number	Descriptive name of the equipment served by this Boiler #3	e equipment se		stack or vent			Approx UTM 2	Approx. location UTM Zone No.	of stack or	vent (see Horiz	(see inst. on how to de Horizontal Coordinate	w to determ dinate	ĕ
]									16	Verti	Vertical Coordinate	nate	3355400 mN
Stack and Discharge Physical Characteristics Change ☐Yes 区No	Height of stack above grade (ft) 90.0	Diameter (ft) or stack discharge area (ft^2) N/A (f	t, 2, 4, 5, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,	Stack gas exit temperature (Deg F)		Stack gas flow at process conditions, not at standard (ft^3/min) 300800	s flow at proci s, not at stanc (ft^3/min) 300800	ess	Stack gas exit velocity (ft/sec) N/A		Date of construction / modification	struction / ation	Operating rate (Max) or tank capacity
	Type of fuel used and heat input	d and heat	input			Percent pollutants	Percent of annual throughput of pollutants through this emission point	throughpuis emissic	ut of an point	Norma	Normal operating time of this point	time	Normal Operating Rate
Fuel	Type of fuel	Heat Inpu	Heat Input (MMBTU/hr)	Operating Characteristics		Dec-Feb Mar-May Jun-Aug	//ar-May		Sep-Nov	hrs/day	days/wk	wk/yr	000
					<del></del>	52	22	52	55	24	7	25	MM BTU/hr
Air Pollutant Sp	Air Pollutant Specific Information							1					
Po	Pollutant	Control	Control	M	<b>Emission Rate</b>	ē.	둅	Emission	Add,	Add, Change,	Conc	entration i	Concentration in gases exiting at stack
	+	Equipment Code	Equipment Efficiency (%)	Average (lbs/hr)	Maximum (lbs/hr)	Annual (tons/yr)		Estimation Method	or Del	or Delete Code			
CARBON MONOXIDE		000	0					7	٥	Delete			
NITROGEN OXIDES		000	0					7	a	Delete			
PARTICULATE MATTER	TER	000	0					7	O	Delete			
SULFUR DIOXIDE		000	0					7	٥	Delete			
TOTAL VOC (INCL. LISTED)	ISTED)	000	0					7	_	Delete		ļ	
TOTAL VOC (INCL. L	ISTED)	ONG.	5				-		_				

Department of Environmental Quality	ronmental Quality				LOU	LOUISIANA	Ϋ́					A STATE OF THE STA
Permits Division P.O.Box 82135	Division 82135		S	SINGLE POINT/AREA/VOLUME SOURCE	DINT/AF	REAVO	LUMES	SOURCE				1 0307 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
Baton Rouge, LA 70884-2135 (225) 765-0219	A 70884-2135 5-0219			Emissio	n Invento for Ai	nventory Questior for Air Pollutants	Emission Inventory Questionnaire (EIQ) for Air Pollutants	(EIQ)				
Company Name			<u>a</u>	Plant location and name (if any)	I name (if an	<u>y</u>						Date of Submittal
The Dow Chem	The Dow Chemical Company, Louisiana Operation	iisiana Op		Power i Plant				Pla	Plaquemine, LA	٩,	_	March 2005
Source ID Number	Descriptive name of the equipment served by this stack or vent	equipment se	rved by this stac	k or vent			Approx. loc	cation of stac	k or vent (s	ee inst. on h	ow to deterr	Approx. location of stack or vent (see inst. on how to determine loc. of area srcs).
71	Boiler #4						UTM Zone No.		5 H	Horizontal Coordinate	ordinate	669900 mE
									16 V	Vertical Coordinate	inate	3355400 mN
Secondario Para James	Height of stack	Diameter (ft) or stack	r stack	Stack gas exit		tack gas flo	Stack gas flow at process	-	Stack gas exit	Date of co	Date of construction /	Operating rate (Max) or
Stack and Discharge Physical	above grade (ft)	discharge area (ff^2)		temperature (Deg F)		anditions, no	conditions, not at standard		velocity (fl/sec)	modif	modification	tank capacity
Characteristics Change ∐Yes ∭No	115.0		N/A (ft) (ft^2)	230		336	336736		A/A			
	Type of fuel used and heat input	d and heat	input			Percent o	Percent of annual throughput of lutants through this emission po	Percent of annual throughput of pollutants through this emission point	ļ	Normal operating time of this point	g time	Normal Operating Rate
Fuel	Type of fuel	Heat Inpu	Heat Input (MMBTU/hr)	Operating					}-	- 1		
	:			Characteristics	_	Jec-reb Mi	ar-may Jun-	Dec-reb Mar-May Jun-Aug Sep-Nov	ov nrsvday	/ gays/wk	WICYI	1603
					L	22	25 2	25 25	24	2	52	MM BTU/hr
				ļ								
Air Pollutant Sp	Air Pollutant Specific Information											
Pol	Pollutant	Control	Control	13	Emission Rate	e	Emission		Add, Change,		centration	Concentration in gases exiting at stack
		Equipment Code	Equipment Efficiency (%)	Average (lbs/hr)	Maximum (lbs/hr)	Annual (tons/yr)	Estimation Method		or Delete Code	e e		
CARBON MONOXIDE	ш	000	0				7		Delete			
NITROGEN OXIDES		000	0				4		Delete			
PARTICULATE MATTER	rer	000	0				2		Delete			
SULFUR DIOXIDE		000	0				7		Delete			
TOTAL VOC (INCL. LISTED)	.ISTED)	000	. 0				7		Delete			

Department of Environmental Quality
Office of Air Quality
Radiation Protection
P. O. Box 82135
Baton Rouge, LA 70884-2135
(225) 765-0195

# **LOUISIANA**

# ERC BANK APPLICATION VOLATILE ORGANIC COMPOUNDS



COMPANY: The Dow	Chemical Company	, Louisiana (	Operations			
LOCATION:	Plaquemine			Iberville		·
Westbank of the	(City) Mississippi River in <u>I</u> b	erville Parish (Physical Location		(Parish) y 1		
MAILING ADDRESS:			Plaquem		LA	70765 (Zip Code)
·	(Street or P. O. Box)		(City)		(State)	(Zip Code)
8.69		0			)	
(ERCs deposited - TPY)	(ERCs relied	d upon for netting -	TPY)	(ERCs relied upon	for offsets -	TPY)
Boiler 3 – 3/12/04 Boiler 4 – 3/19/04		8.69		8	69	<del></del>
(Date of Emissions Increase/Decre	ease) (ERCs av	ailable for netting –	TPY)	(ERCs available	for offsets -	TPY)
NOTE: Power I Plant's		ECTED PER	RMIT	· · · · · · · · · · · · · · · · · · ·		
Permit Number:3	85 (M-3)	Facility:	Power I Plant			
Affected EIQ Source ID	No. (s): 1E: Boiler 3	and 1F: Boile	er 4			
I hereby certify that the accurate to the best of m		in this ERC I	Bank Applicatio	n and calculat	ions is tr	ue and
Gretchen Leblan	nc	Productio	n Leader	(225)-3	53-1642	
(Name)		-	(Title)	(Te	lephone Nur	mber)
Gignature)	Celslane_	$3/2^{2}$	105			
(Signature)		(22.0)				

Department of Environmental Quality
Office of Air Quality
Radiation Protection
P. O. Box 82135
Baton Rouge, LA 70884-2135
(225) 765-0195

# **LOUISIANA**

# ERC BANK APPLICATION Oxides of Nitrogen



COMPANY: The Dow	Chemical Company, I	<u> Louisiana Operatio</u>	ns						
LOCATION:	Plaquemine		Ibervi						
	(City)		(Parisl	1)					
Westbank of the	Mississippi River in Iber	ville Parish on LA Physical Location)	Highway 1						
MAILING ADDRESS		•	1	T A	70765				
MAILING ADDRESS:	(Street or P. O. Box)	<u>P</u> .	laquemine (City)	LA (State)	70765 (Zip Code)				
2336		39.3		854.4 <sup>1</sup>					
(ERCs deposited – TPY)	(ERCs relied up	oon for netting – TPY)	(ERCs relied t	ipon for offsets -	TPY)				
Boiler 3 – 3/12/04 Boiler 4 – 3/19/04		342.4		342.4					
	(Date of Emissions Increase/Decrease) (ERCs available for netting – TPY) (ERCs available for offsets – TPY)  Allotted to Venture's Lease Co., LLC								
COMMENTS  ERC No: NOx-9  NOTE: Power I Plant's Boiler 3 and 4.									
	AFFE	CTED PERMIT							
Permit Number:38	35 (M-3)	Facility: Power	I Plant						
Affected EIQ Source ID	No. (s): 1E: Boiler 3 as	nd 1F: Boiler 4							
I hereby certify that the accurate to the best of m		this ERC Bank App	plication and calcu	ulations is tr	rue and				
Gretchen Leblan	c P	roduction Leader	(22	25)-353-164	2				
(Name)		(Title)		(Telephone Nur	nber)				
Grechhen Cle (Signature)	Slane	3/33/05 (Date)							

#### Emissions Summary Boiler 3&4

	1999	2000	Average
	Actual	Actual	2-yr Actual
	Emissions	Emissions	Emissions
	(tpy)	(tpy)	(tpy)
NOx			
Boiler 3 (EIQ 1E)	1233.70	1208.74	
Boiler 4 (EIQ 1F)	1208.02	1021.59	
Total	2441.71	2230.33	2336.02
voc			
Boiler 3 (EIQ 1E)	3.43	3.55	
Boiler 4 (EIQ 1F)	5.43	4.96	
Total	8.87	8.51	8.69
SO2			
Boiler 3 (EIQ 1E)	3.51	3.63	
Boiler 4 (EIQ 1F)	5.55		
Total	9.06	8.69	8.87
PM10			· <del>-</del>
Boiler 3 (EIQ 1E)	12.26		
Boiler 4 (EIQ 1F)	19.40	· ·	
Total	31.67	30.38	31.02
CO	1		
Boiler 3 (EIQ 1E)	492.59	509.20	
Boiler 4 (EIQ 1F)	155.21	141.58	
Total	647.79	650.78	649.29
Methane	674		
Boiler 3 (EIQ 1E)	0.74	0.76	
Boiler 4 (EIQ 1F)	1.16	1.06	
Total	1.90	1.82	1.86

# **BOILER 3**

```
DESCRIPTION:
                                1E
SOURCE ID:
                                BOILER#3
BASIS AND CALCULATIONS:
Fire Duty:
                                         5,151,129 MMBTU/yr
Days in Operation:
                                                365 days
Excess O2 in Flue (Wet Basis):
                                                  5 Mole %
Stack Temperature:
                                                250 Deg F
Stack Diameter:
                                                 12 Feet
Fuel Type:
                                Natural Gas
Heating Value:
                                               1050 Btu/SCF
Emission Factors:
                        PM10:
                                               5.00 lb/MMSCF
                                                                     Derived from standard AP-42 calculations
                          SOx:
                                               1.43 lb/MMSCF
                                                                     Dow Natural Gas Contract
                  Non-Methane:
                                                1.4 lb/MMSCF
                                                                     Derived from standard AP-42 calculations
                       Methane:
                                                0.3 lb/MMSCF
                                                                     Derived from standard AP-42 calculations
                           CO:
                                                200 ppmv(wet)
                                                                     Based on Operating Experience
                          NOx:
                                              0.479 lb/MMBTU
                                                                     Based on 1999 Operating Data
             PM10 Emissions = PM10 Emission Factor / Heating value * Fire Duty
                              = 5.00 lb/MMSCF * 1 SCF/1050.0 Btu * 5.15e+6 (MM Btu/yr)
                                          24529.186 lb/yr
                                              12.26 tons/yr
               SOx Emissions = SOx Emission Factor / Heating value * Fire Duty
                              = 1.43 lb/MMSCF * 1 SCF/1050.0 Btu * 5.15e+6 (MM Btu/yr)
                                          7015.347 lb/yr
                                               3.51 tons/yr
                CO Emissions = CO Conc * Flue Gas Flow
                              = 200 (ppm) * (1/10<sup>6</sup>) *0.3484E+05(lb_mole/hr) * (28 lb/1b_mole)
                                          985173.84 lb/yr
                              =
                                             492.59 tons/yr
                              =
               NOx Emissions = NOx Emission Factor * Fire Duty
                              = 0.479 lb/MMSCF * 5.15e+6 (MM Btu/yr)
```

2467390.791 lb/yr 1233.70 tons/yr DESCRIPTION: 1E

SOURCE ID: BOILER # 3

#### **BASIS AND CALCULATIONS:**

Fire Duty: 5,324,864 MMBTU/yr
Days in Operation: 365 days

Excess O<sub>2</sub> in Flue (Wet Basis): 5 Mole %
Stack Temperature: 250 Deg F
Stack Diameter: 12 Feet

Fuel Type: Natural Gas

Heating Value: 1050 Btu/SCF

**Emission Factors:** 

PM10: 5.00 Ib/MMSCF Derived from standard AP-42 calculations SOx: Dow Natural Gas Contract 1.43 lb/MMSCF Non-Methane: Derived from standard AP-42 calculations 1.4 lb/MMSCF Methane: 0.3 lb/MMSCF Derived from standard AP-42 calculations CO: 200 ppmv(wet) Based on Operating Experience NOx: 0.454 lb/MMBTU Based on 2000 Operating Data

PM10 Emissions = PM10 Emission Factor / Heating value \* Fire Duty

= 5.00 lb/MMSCF \* 1 SCF/1050.0 Btu \* 5.32e+6 (MM Btu/yr)

= 25356.495 lb/yr = 12.68 tons/yr

SOx Emissions = SOx Emission Factor / Heating value \* Fire Duty

= 1.43 lb/MMSCF \* 1 SCF/1050.0 Btu \* 5.32e+6 (MM Btu/yr)

= 7251.958 lb/yr = 3.63 tons/yr

CO Emissions = CO Conc \* Flue Gas Flow

= 46.94 (ppm) \* (1/10^6) \*0.3484E+05(lb\_mole/hr) \* (28 lb/1b\_mole)

= 1018401.35 lb/yr = 509.20 tons/yr

NOx Emissions = NOx Emission Factor \* Fire Duty

= 0.454 lb/MMSCF \* 5.32e+6 (MM Btu/yr)

= 2417488.256 lb/yr = 1208.74 tons/yr

THCLM Emissions = THCLM Emission Factor / Heating value \* Fire Duty

= 1.400 lb/MMSCF \* 1 SCF/1050 Btu \* 5.32e+6 (MM Btu/yr)

= 7099.819 lb/yr = 3.55 tons/yr

Methane Emissions = Methane Emission Factor / Heating value \* Fire Duty

= 0.3000 lb/MMSCF \* 1 SCF/1050.0 Btu \* 5.32e+6 (MM Btu/yr)

= 1521.390 lb/yr = 0.76 tons/yr



DESCRIPTION:

1F

SOURCE ID:

**BOILER #4** 

#### **BASIS AND CALCULATIONS:**

Fire Duty:

8,388,996 MMBTU/yr

Days in Operation:

365 days

Fuel Type:

Natural Gas

Heating Value (Avg): Heating Value (Min): 1081 Btu/SCF 1050 Btu/SCF

Stack Flowrate @ 32F:

355772 SCFM (Testing 3/23/88)

#### **Emission Factors:**

CO:

40 lb/MMSCF

Derived from standard AP-42 calculations

PM10: SOx: 5.00 lb/MMSCF

Derived from standard AP-42 calculations

Non-Methane (VOC):

1.43 lb/MMSCF

Dow Natural Gas Contract Derived from standard AP-42 calculations

Methane:

1.4 lb/MMSCF

Derived from standard AP-42 calculations

NOx:

0.3 lb/MMSCF 0.288 lb/MMBTU

Based on 1999 Operating Data

PM10 Emissions = PM10 Emission Factor / Heating value \* Fire Duty

= 5.00 lb/MMSCF \* 1 SCF/1081.0 Btu \* 8.39e+6 (MM Btu/yr)

38802.017 lb/yr

19.40 tons/yr

SOx Emissions = SOx Emission Factor / Heating value \* Fire Duty

= 1.43 lb/MMSCF \* 1 SCF/1081.0 Btu \* 8.39e+6 (MM Btu/yr)

11097.377 lb/yr

5.55 tons/yr

CO Emissions = CO Emission Factor / Heating value \* Fire Duty

= 40.0 lb/MMSCF \* 1 SCF/1081.0 Btu \* 8.39e+6 (MM Btu/yr)

310416.13 lb/yr

= 155.21 tons/yr

VOC Emissions = VOC Emission Factor / Heating value \* Fire Duty

= 1.4 lb/MMSCF \* 1 SCF/1081 Btu \* 8.39e+6 (MM Btu/yr)

10864.565 lb/yr

5.43 tons/yr =

Methane Emissions = Methane Emission Factor / Heating value \* Fire Duty

= 0.30 lb/MMSCF \* 1 SCF/1081.0 Btu \* 8.39e+6 (MM Btu/yr)

2328.121 lb/yr

1.16 tons/yr

NOx Emissions = NOx Emission Factor \* Fire Duty

= 0.288 lb/MMSCF \* 8.39e+6 (MM Btu/yr)

2416030.848 lb/yr

1208.02 tons/yr

DESCRIPTION: 1F

SOURCE ID: BOILER # 4

#### BASIS AND CALCULATIONS:

Fire Duty: 7,652,348 MMBTU/yr

Days in Operation: 365 days

Fuel Type:

Natural Gas

Heating Value (Avg): Heating Value (Min): 1081 Btu/SCF 1050 Btu/SCF

Stack Flowrate @ 32F:

355772 SCFM (Testing 3/23/88)

**Emission Factors:** 

CO: 40 lb/MMSCF Derived from standard AP-42 calculations

PM10: 5.00 lb/MMSCF Derived from standard AP-42 calculations

SOx: 1.43 lb/MMSCF Dow Natural Gas Contract

Non-Methane (VOC): 1.4 lb/MMSCF Derived from standard AP-42 calculations

Methane: 0.3 lb/MMSCF Derived from standard AP-42 calculations

NOx: 0.267 lb/MMBTU Based on 1999 Operating Data

PM10 Emissions = PM10 Emission Factor / Heating value \* Fire Duty

= 5.00 lb/MMSCF \* 1 SCF/1081.0 Btu \* 7.65e+6 (MM Btu/yr)

= 35394.764 lb/yr = 17.70 tons/yr

SOx Emissions = SOx Emission Factor / Heating value \* Fire Duty

= 1.43 lb/MMSCF \* 1 SCF/1081.0 Btu \* 7.65e+6 (MM Btu/yr)

= 10122.903 lb/yr = 5.06 tons/yr

CO Emissions = CO Emission Factor / Heating value \* Fire Duty

= 40.0 lb/MMSCF \* 1 SCF/1081.0 Btu \* 7.65e+6 (MM Btu/yr)

= 283158.11 lb/yr = 141.58 tons/yr

VOC Emissions = VOC Emission Factor / Heating value \* Fire Duty

= 1.4 lb/MMSCF \* 1 SCF/1081 Btu \* 7.65e+6 (MM Btu/yr)

= 9910.534 lb/yr = 4.96 tons/yr

Methane Emissions = Methane Emission Factor / Heating value \* Fire Duty

= 0.30 lb/MMSCF \* 1 SCF/1081.0 Btu \* 7.65e+6 (MM Btu/yr)

= 2123.686 lb/yr = 1.06 tons/yr

NOx Emissions = NOx Emission Factor \* Fire Duty

= 0.267 lb/MMSCF \* 7.65e+6 (MM Btu/yr)

= 2043176.916 lb/yr = 1021.59 tons/yr